



DESCRIPTION

SPLASH is a clear single component Water Based free flowing liquid developed specially for a waterproofing of very difficult areas, where in other waterproofing systems cannot be implemented. **SPLASH** is ready to use material available in white turbid color, which penetrates in to the pores. It dries to a clear and tough film which gives high quality waterproofing

PROPERTIES

Specific gravity	: 1.03
Viscosity	: 15-20 sec.
Solid Content	: 32+2%
Surface Dry	: 10-20 Min.
Complete curing	: 24 Hrs.
Coverage	
On concrete surface (On Throwing)	: 15-20 sq.ft/ltr./2coats @ 70-75 μ
On Asbestos Surface (on Brushing)	: 80-90 sq.ft/ltr./2coats @ 60 μ
On Stone (On Brushing)	

KEY PROPERTIES

- **SPLASH** is having a very good penetration property.
- **SPLASH** is having excellent fast setting property.
- **SPLASH** is having very good UV resistance.
- **SPLASH** is having good abrasion resistance.

APPLICATIONS


- It can be poured on the areas of terraces where in normal case waterproofing is difficult.
- It can be applied on terraces where already china chips are fixed. **SPLASH** fills the joints on the china chips and forms a hard and tough transparent film.
- It can be applied on the parapet walls by brushing.
- It can be applied on bricks as well as on stone walls
- It can be applied on building exterior walls on the painted surface to provide extra gloss and waterproofing of the walls.

PROCESS OF APPLICATION

- If it is to be applied on concrete surface then first clean the concrete surface with the help of wire brush.
- See to that it should be free from the loose particles, pour the **SPLASH** on the area where it is to be applied.

■ SPLASH

WATERPROOFING LIQUID FOR UNREACHABLE AREAS



- Please do the masking on the corners of the areas where it is poured.
- Please spread the liquid with the help of mop or brushes if required.

METHOD OF APPLICATION

- Remove the masking tapes after the surface is dried.
- On vertical walls please clean the walls with moist cloth and let it dry for a while.
- Apply SPLASH first coat on the area, wait for min one hour between two coats of the tech splash.
- On bricks, three coats are recommended because first coat is getting penetrated to seal the Pores.
- After that apply two more coats to get the desired properties.

STORAGE CONDITIONS

- keep the material in temp condition of $30 \pm 5^{\circ}\text{C}$

SHELF LIFE

2 yrs from the date of mfg.

PACK SIZE

1 Liter, 5 Liters, and 20 Liters.